



# sCELL-EF

## LTE Enterprise Femtocell

2 x 2 MIMO

2 x 125mw

32 Concurrent Users

64 RRC Connected Users

The sCELL-EF from BTI WIRELESS is an enterprise-level 4G integrated Femto applying LTE technology. The product connects to the backbone network through wired backhaul and provides LTE access for terminals. It supports the transmission of voice and data with indoor wireless broadband coverage.

## KEY FEATURES

- Integrated design of baseband and radio head
- Based on 3GPP LTE technology with high-speed data services
- Supports 5 MHz, 10 MHz, 15 MHz, 20 MHz bandwidth
- Convenient networking, plug and play solution, easy and flexible deployment
- External high-gain antenna for various usage scenarios
- Built-in DHCP server, DNS client and NAT functions, powerful high-speed routing capabilities
- Plentiful security service provides real-time protection, to prevent potential security risks and illegal intrusion
- Web-based management, convenient and intuitive
- Complete network management function
- Humanized indicator light, easy to observe and manage equipment status
- IP20 protection level

## APPEARANCE



## INTERFACE SPECIFICATIONS

INTERFACE NAME	QUANTITY	INTERFACE TYPE	INTERFACE DEFINITION
WAN/ PoE	1	RJ45	Data return and PoE+ power supply interface
LAN	1	RJ45	Local debugging interface
USIM	1		USIM card slot
SFP (Optional)	1	SFP	Data transmit back to optical interface
DC 12V	1	DC Socket	12V DC power supply interface
RST	1		Manual reset device button
GPS	1	SMA	GPS antenna interface

## HARDWARE SPECIFICATIONS

Work Style	LTE FDD
------------	---------

<b>Working Frequency</b>	B1/3
<b>Working Bandwidth</b>	5 MHz/ 10 MHz/ 15 MHz/ 20 MHz
<b>Transmit Power</b>	2 x 21 dBm
<b>Synchronization</b>	Supports GPS, and air interface synchronization
<b>Backhaul Method</b>	RJ-45 ethernet port (1GE), SFP optical port
<b>MIMO</b>	2 x 2
<b>Equipment Size</b>	220 x 220 x 39 mm   8.66 x 8.66 x 1.54 in
<b>Installation Method</b>	Wall hanging, ceiling, desktop
<b>Power Consumption</b>	< 15W
<b>Power Supply</b>	220V AC to 12V DC power adapter, PoE+
<b>Weight</b>	< 0.65 kg   1.43 lbs
<b>Equipment Capacity</b>	< 1.9 L

## SOFTWARE SPECIFICATIONS

<b>Technical Standard</b>	3GPP Release 12
<b>Peak Rate (20 MHz Bandwidth)</b>	DL: 150 Mbps (64QAM)/ UL: 75 Mbps (64QAM)
<b>Operational Capacity</b>	Supports 32 concurrent users, 64 RRC connected users
<b>Scheduling Method</b>	3GPP standard QCI
<b>Modulation</b>	Downlink: QPSK, 16QAM, 64QAM Uplink: QPSK, 16QAM, 64QAM
<b>Voice Solution</b>	VoLTE
<b>SON</b>	Supports automatic configuration, ANR and PCI conflict detection
<b>Network Management Interface</b>	Supports TR069 interface protocol
<b>MTBF</b>	< 150,000 hours
<b>MTTR</b>	< 1 hour
<b>O&amp;M</b>	<ul style="list-style-type: none"> <li>Remote/local maintenance, based on SSH protocol</li> <li>Online status management</li> <li>Performance statistics</li> <li>Fault management</li> <li>Configuration management</li> <li>Local or remote software upgrade and loading</li> <li>Supports log</li> <li>Connectivity diagnosis</li> <li>Self-start and self-configuration deployment</li> <li>Alarm reporting</li> <li>Supports KPI reporting</li> <li>User information tracking</li> </ul>

**ENVIRONMENTAL SPECIFICATIONS**

<b>Operating Temperature</b>	-5 °C ~ +45 °C   +23 °F ~ +113 °F
<b>Humidity</b>	10% ~ 95%

Contact Us

[www.btiwireless.com](http://www.btiwireless.com)[sales@btiwireless.com](mailto:sales@btiwireless.com)